

集装袋 FIBC

类型Bag Type: 卷式或折叠式ROLL Or FLAT BAG

吊环LOOP: 单环、双环或五环ONE LOOP Or TWO LOOPS OR FIVE LOOPS

外层材质Out Bag Material: PP编织PP Woven

内层材质Inner Bag Material: PE或PP编织PP Woven

(热合Heat sealing或缝线Stitching)



设备参数 Equipment parameters

包装 Packing	每包重量Net weight per bag: 500-1500kg 包装速度Packing speed: 20-100 Bags/Hour 包装精度Accuracy: ±1/1000-2000kg *包装速度和包装精度的具体数值, 依赖于产品的流动性和灌装重量depending on product flow ability and filling weight
卷筒尺寸 Reel Size	空筒尺寸Inner core size: 内径Inner diameter 290mm, 外径outer diameter 315mm 满卷尺寸Full roll size: 外径Outer diameter 1200mm (每卷80-120条集装袋80-120 bags per roll)
设备特征 Features	<input type="checkbox"/> 卷筒自动上下料 Automatic reel loading and unloading <input type="checkbox"/> 自动均匀收绳 Automatic and uniform rope winding <input type="checkbox"/> 自动套袋 Automatic bag sleeving <input type="checkbox"/> 自动吹气胀袋 Automatic air inflation for bag expansion <input type="checkbox"/> 净重称 (或下称重、下振动) Net weighing (or bottom weighing, bottom vibration) <input type="checkbox"/> 袋口热合 (或缝线、扎口) Bag mouth heat sealing (or stitching, tying) <input type="checkbox"/> 叉车叉取时, 无需人工辅助挂袋 No manual assistance is required for bag hanging when the forklift is picking up. <input type="checkbox"/> 选配吨袋整形卷袋机, 确保预开袋成功率 Optional Jumbo bag shaping and rolling machine ensures the success rate of pre-opening bags.

核心配件 Core accessories

称重传感器 Load cell				
电机 Motor				
气缸 Cylinder				
轴承 Bearing				
电气元件 Electrical components				
PLC / HMI				

合肥正远智能包装科技有限公司

地址: 合肥肥西桃花工业园拓展区黄岗路泰禾产业园北门

内贸: 0551 68268887

外贸: +86 551 68758887

邮箱: hfzypack@hfzyzn.cn

网址: www.hfzyzn.cn



正远包装公众号



正远qq营销号



正远官方抖音号